MEECO MFG CO INC SAFETY DATA SHEET **Insulating Cement**

1. Identification

Product identifier Insulating Cement

Other means of identification

Brand Code 623

Recommended use Castable brick mix

Recommended restrictions Users should be informed of the potential presence of respirable dust and respirable crystalline

silica as well as their potential hazards. Appropriate training in the proper use and handling of this

Category1A Category2

material should be provided as required under applicable regulations.

Manufacturer/Supplier information

Manufacturer

MEECO MFG CO INC Company name 9100 5th PI S., Suite E Address Seattle, WA 98108 US

General Phone: 206.262.8340 Telephone

www.meecomfg.com Website

Emergency phone number MEECO MFG CO INC 1-800-426-9393

2. Hazard(s) identification

Physical hazards Not classified. Health hazards Carcinogenicity

Specific target organ toxicity, repeated

exposure

Environmental hazards Not classified. OSHA defined hazards Not classified.

Label elements



Signal word Danger

May cause cancer. May cause damage to organs through prolonged or repeated exposure. Hazard statement

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safetyprecautions have been read

and understood. Do not breathe dust/mist. Do not breathe dust. Wear protective gloves/protective

clothing/eye protection.

Response If concerned: Get medical advice/attention. Get medical advice/attention if you feel unwell.

Storage Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations. Disposal

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information Users should be informed of the potential presence of respirable dust and respirable crystalline

silica as well as their potential hazards. Overexposure to the respirable dust of crystalline silica (quartzor cristobalite, less than or equal to 5 microns in size) may lead to silicosis in humans, which is a progressive and irreversible lung disease. Appropriate training in the proper use and

handling of this material should be provided as required under applicable regulations.

Composition/information on ingredients

Mixtures

Material name: Insulating Cement SDS US

Chemical name	Common name and synonyms	CAS number	%
Cement, Alumina, Chemicals		65997-16-2	20 - 40
Mullite		1302-93-8	20 - 40
Amorphous Silica	SILICA, AMORPHOUS, FUMED SILICA (CRYSTALLINE FREE)	7631-86-9	2.5 - 10
Cristobalite		14464-46-1	2.5 - 10
Quartz(SiO2)		14808-60-7	2.5 - 10
Fumes, Silica		69012-64-2	1 - 2.5
Aluminium Oxide (Non-Fibrous)		1344-28-1	0 - 0.1
Other components below reportable levels			20 - 40

^{*}Designates that a specific chemical identityand/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Do not rub eyes. Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

effects.

Most important

symptoms/effects, acute and delayed

Indication of immediate

medical attention and special treatment needed

General information

Provide general supportive measures and treat symptomatically. Keep victim under observation.

Dusts may irritate the respiratory tract, skin and eyes. Prolonged exposure may cause chronic

Symptoms maybe delayed.

If concerned: Get medical advice. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters

Use fire-extinguishing media appropriate for surrounding materials.

Not available.

Not applicable.

Not available.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessarypersonnel away . Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe dust. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Stop the flow of material, if this is without risk. Collect dust using a vacuum cleaner equipped with HEPA filter.

Large Spills: Wet down with water and dike for later disposal. Shovel the material into waste container. Following product recovery, flush area with water.

Small Spills: Sweep up or vacuum up spillage and collect in suitable container for disposal.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

Environmental precautions7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Minimize dust generation and accumulation. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Do not breathe dust. Avoid prolonged exposure. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Store locked up. Store in original tightlyclosed container. Store in a well-ventilated place. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-3 (29 CF Components	Type	Value	Form
Amorphous Silica (CAS 7631-86-9)	TWA	0.8 mg/m3	
		20 mppcf	
Cristobalite (CAS 14464-46-1)	TWA	0.15 mg/m3	Total dust.
,		0.05 mg/m3	Respirable.
		1.2 mppcf	Respirable.
Fumes, Silica (CAS 69012-64-2)	TWA	0.8 mg/m3	
	TWA	20 mppcf	
Quartz(SiO2) (CAS 14808-60-7)	IWA	0.3 mg/m3	Total dust.
		0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.
US. ACGIH Threshold Limit	Values		
Components	Туре	Value	Form
Cristobalite (CAS 14464-46-1)	TWA	0.025 mg/m3	Respirable fraction.
Mullite (CAS 1302-93-8)	TWA	1 mg/m3	Respirable fraction.
Quartz(SiO2) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
US. NIOSH: Pocket Guide to	Chemical Hazards		
Components	Туре	Value	Form
Amorphous Silica (CAS 7631-86-9)	TWA	6 mg/m3	
Cristobalite (CAS 14464-46-1)	TWA	3 fibers/cm3	Fiber.
,		3 fibers/cm3	Dust.
		5 mg/m3	Fiber, total
		5 mg/m3	fibers, total dust
Fumes, Silica (CAS	TWA	6 mg/m3	
69012-64-2) Quartz(SiO2) (CAS	TWA	0.05 mg/m3	Respirable dust.
14808-60-7) logical limit values	No biological exposure limits noted t	for the ingredient(s)	
· ·	Occupational exposure to nuisance	· · · · · · · · · · · · · · · · · · ·	penirable ervetalling cilias
osure guidelines	should be monitored and controlled.	, ,	,
propriate engineering trols	Good general ventilation (typically10 should be matched to conditions. If or other engineering controls to main exposure limits have not been estable engineering measures are not suffic Occupational Exposure Limit (OEL), ground, cut, or used in anyoperation ventilation to keep exposures below	applicable, use process enclosuration airborne levels below recorblished, maintain airborne levels ient to maintain concentrations of suitable respiratoryprotection may which may generate dusts, use	res, local exhaust ventilation mended exposure limits. to an acceptable level. If of dust particulates below the worn. If material is appropriate local exhaust
vidual protection measures, s Eye/face protection	uch as personal protective equipment Chemical respirator with organic var	por cartridge, full face piece, dus	t and mist filter.
Skin protection			
Hand protection	Wear appropriate chemical resistant	gloves.	
Other	Use of an impervious apron is recon	nmended.	
–			

Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels

exceeding the exposure limits.

Respiratory protection

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.









General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Solid. Physical state

Form Solid Powder. Not available. Color Not available. Odor Not available. Odor threshold Not available. pΗ Not available. Melting point/freezing point Initial boiling point and boiling

range

Not available.

Not available. Flash point Not available. Evaporation rate Not available. Flammability (solid, gas)

Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

Not available.

(%)

Flammability limit - upper

(%)

Not available. Explosive limit - lower (%)

Explosive limit - upper (%) Not available.

Not available. Vapor pressure Not available. Vapor density Relative density Not available.

Solubility(ies)

Not available. Solubility (water) Not available. Partition coefficient

(n-octanol/water)

Not available. Auto-ignition temperature Not available. Decomposition temperature Viscosity Not available.

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Material is stable under normal conditions. Chemical stability

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Powerful oxidizers. Chlorine. Incompatible materials

Incompatibility is based strictly upon potential theoretical reactions between chemicals and may

not be specific to industrial application exposure. Contact your sales representative for

Hazardous decomposition

products

No hazardous decomposition products are known.

Material name: Insulating Cement

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause damage to organs through prolonged or repeated exposure by inhalation. Dust may

irritate respiratory system. Prolonged inhalation maybe harmful.

Skin contact Dust or powder may irritate the skin.

Eye contact Dust may irritate the eyes.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Dusts may irritate the respiratory tract, skin and eyes.

Information on toxicological effects

Acute toxicity Not available.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity In 1997, IARC (the International Agencyfor Research on Cancer) concluded that crystalline silica

inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activityor distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker

protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. May cause cancer. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled.

IARC Monographs. Overall Evaluation of Carcinogenicity

Amorphous Silica (CAS 7631-86-9) 3 Not classifiable as to carcinogenicity to humans.

Cristobalite (CAS 14464-46-1) 1 Carcinogenic to humans.

Fumes, Silica (CAS 69012-64-2) 3 Not classifiable as to carcinogenicity to humans.

Quartz (SiO2) (CAS 14808-60-7) 1 Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens

Cristobalite (CAS 14464-46-1) Known To Be Human Carcinogen.

Reasonably Anticipated to be a Human Carcinogen.

Quartz (SiO2) (CAS 14808-60-7) Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Developmental effects

Quartz (SiO2) 0
Developmental effects - EU category

Quartz (SiO2)

Embryotoxicity
Quartz (SiO2)
0

Reproductivity
Ouartz(SiO2)

Quartz(SiO2)

Specific target organ toxicity -

single exposure

Not classified.

Material name: Insulating Cement
211C Version #: 01 Issue date: 03-16-2016

Specific target organ toxicity -

repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard Not an aspiration hazard.

Chronic effects May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may

be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

The product is not classified as environmentally hazardous. However, this does not exclude the **Ecotoxicity**

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

No data available.

Mobility in soil

No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions This product, in its present state, when discarded or disposed of, is not a hazardous waste

> according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria

for hazardous waste.

Since this product is used in several industries, no Waste Code can be provided by the supplier. Hazardous waste code

The Waste Code should be determined in arrangement with your waste disposal partner or the

responsible authority.

Waste from residues / unused

products

Not available.

Contaminated packaging

Not available.

Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and Not available.

the IBC Code

15. Regulatory information

This product is not a "Hazardous Chemical" as defined by the OSHA Hazard Communication US federal regulations

Standard, 29 CFR 1910.1200.

One or more components are not listed on TSCA.

All chemical substances in this product are listed on the TSCA chemical substance inventory

where required.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

SARA 304 Emergency release notification

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Immediate Hazard - No Hazard categories

Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

Material name: Insulating Cement

SDS US 6/8 SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. Massachusetts RTK - Substance List

Amorphous Silica (CAS 7631-86-9) Cristobalite (CAS 14464-46-1) Fumes, Silica (CAS 69012-64-2)

Quartz (SiO2) (CAS 14808-60-7)

US. New Jersey Worker and Community Right-to-Know Act

Amorphous Silica (CAS 7631-86-9) Cristobalite (CAS 14464-46-1) Fumes, Silica (CAS 69012-64-2) Quartz (SiO2) (CAS 14808-60-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Amorphous Silica (CAS 7631-86-9) Cristobalite (CAS 14464-46-1) Fumes, Silica (CAS 69012-64-2) Quartz (SiO2) (CAS 14808-60-7)

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Inventory name

Quartz(SiO2) (CAS 14808-60-7) Listed: October 1, 1988 Titanium Dioxide (CAS 13463-67-7) Listed: September 2, 2011

International Inventories

Country(s) or region

Australia	Australian Inventoryof Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventoryof Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventoryof Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventoryof Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventoryof Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

Toxic Substances Control Act (TSCA) Inventory United States & Puerto Rico *A "Yes" indicates that all components of this product complywith the inventoryrequirements administered bythe governing country(s)

Material name: Insulating Cement

On inventory (yes/no)*

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventoryadministered bythe governing country(s).

16. Other information, including date of preparation or last revision

03-16-2016 Issue date

Version #

Disclaimer

This information is based on our present knowledge on creation date. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Material name: Insulating Cement SDS US